

Product Data Sheet

Manufacturer : Alnor

Model : LoFlo Balometer

Page 1 of 1



LoFlo Balometer®

The LoFlo Balometer is ideal way to measure very low volumetric flow.

You can confidently and accurately measure from 10-500 cfm. It's a great lightweight instrument for residential or commercial use.

The LoFlo Balometer can be used with, or without, capture hoods giving the instrument a very low profile.

Range	10 -500 cfm
Resolution	1 cfm
Accuracy	± (3% of reading + 2 cfm)
Height	15.5", base only 34.5" with 2' x 2' hood
Weight	4.8 lbs, base only 6.5 lbs with 2' x 2' hood
Base diameter opening	13.3" diameter
Hood sizes available	2' x 2' and 16" x 16"
Display	3.5 digit, 0.44" high, digital display with 26 segment simulated analogue display

Whilst every effort has been made to ensure the accuracy of the information given in this data sheet, no liability is given or implied for any error or omission contained herein. Due to our policy of progressive improvement, **BSRIA Instrument Solutions** reserve the right to change products and/or services without notice. Accuracies shown above are for those stated by the manufacturer, **BSRIA Instrument Solutions** accuracies for Hire instrumentation may differ from those claimed by the manufacturer.

Many names used in this data sheet are the trade mark names of their manufactures; **BSRIA Instrument Solutions** acknowledges all registered trade marks.